



CCI / SPEER

MATERIAL SAFETY DATA SHEET

SECTION 1. MANUFACTURER INFORMATION

MANUFACTURED BY: CCI/SPEER

ADDRESS: 2299 Snake River Avenue
Lewiston, Idaho 83501

TELEPHONE #: (208) 746-2351 (24 HOURS)

EMERGENCY CONTACT: Chief Chemist or Safety Department

TRANSPORTATION EMERGENCY CONTACT: CHEMTREC 1-800-424-9300

MSDS DATE: 11/19/85 **REVIEW DATE:** 8/20/07 **REVISION DATE:** 8/20/07

SECTION 2. PRODUCT INFORMATION

PRODUCT NAME: Powerloads

SYNONYMS:

FORMULA NA **C.A.S.#** NA

DOT PROPER SHIPPING NAME: Cartridges, Power Device

UNITED NATIONS (UN) DESIGNATION: 0323 **HAZARD CLASSIFICATION:** 1.4S (ORM-D Domestic)

NFPA: **HEALTH:** **FLAMMABILITY:** **REACTIVITY:** **SPECIAL:** **EXPLOSIVE**

HAZARDOUS INGREDIENTS **PERCENT** **CAS NUMBER** **UEL/LEL** **EXPOSURE LIMITS**

Copper * +		7440-50-8	NE	1 MG/M ³
Zinc * +		7440-66-6	NE	5 MG/M ³ (Resp. Dust)
Nitrocellulose		9004-20-0	NE	NA
Nitroglycerin *		5563-0	NE	0.2 PPM Ceiling
Barium		10022-31-8	NE	0.5 MG/M ³
Lead Styphnate		15245-44-0	NE	0.05 MG/M ³

NA = NOT AVAILABLE NE = NOT ESTABLISHED MG/M³ = MILLIGRAMS PER CUBIC METER OF AIR
PPM = PARTS PER MILLION REFERENCE OSHA 29 CFR 1910.1000 TABLE Z-1

(*) INDICATES TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 AND 40 CFR 372.

(+) CERTAIN COMPONENTS LISTED IN THE INGREDIENTS SECTION INCLUDE CASE MATERIAL, PROJECTILE OR OTHER INERT COMPONENTS AND ARE NOT EXPECTED TO BE AN EXPOSURE HAZARD UNDER NORMAL HANDLING CONDITIONS.



SECTION 3. PHYSICAL HAZARDS

COMBUSTIBLE LIQUID	NO	SKIN HAZARD	YES
FLAMMABLE	NO	EYE HAZARD	YES
PYROPHORIC	NO	TOXIC AGENT	NO
EXPLOSIVE	YES	SENSITIZER	NO
UNSTABLE	NO	CARCINOGEN	NO
WATER REACTIVE	NO	REPRODUCTIVE TOXIN	NO
OXIDIZER	YES	BLOOD TOXIN	NO
ORGANIC PEROXIDE	NO	NERVOUS SYSTEM TOXIN	NO
CORROSIVE	NO	LUNG TOXIN	NO
COMPRESSED GAS	NO	LIVER TOXIN	NO
IRRITANT	YES	KIDNEY TOXIN	NO

POTENTIAL HEALTH EFFECTS

INHALATION: After powerloads have been fired, dust, vapors, and/or fumes may be irritating to the respiratory system and can result in both acute and chronic overexposure. *

INGESTION: When powerloads are fired or otherwise discharged, dust, vapors, and/or fumes may be absorbed by the digestive system and can result in both acute and chronic overexposure. * Ingestion of a complete round can cause irritation to the digestive system, and possibly other unknown health effects.

SKIN CONTACT: After powerloads have been fired, dust, vapors, and/or fumes may cause irritation.

SKIN ABSORPTION: Not likely to occur.

EYE CONTACT: After powerloads have been fired, dust, vapors, and/or fumes may cause irritation. *

ACCIDENTAL INJURY FROM FIRED CARTRIDGE: Fired powerloads can create serious injury. To avoid serious injury, use ammunition only in good condition and originally chambered for a particular caliber. Always keep the barrel free of any obstruction. If the tool fails to fire, a delayed firing may occur, or the tool may fire upon being opened. Wait 30 seconds. Avoid exposure to breech. Carefully unload.

All hazards marked with an asterisk (*) are not expected to be present unless the product is fired, or otherwise discharged so that gasses, fumes, or projectiles are created. Normal handling and shipping should not cause exposure to these hazards. Lead and its inorganic compounds are neurotoxins that may produce neuropathy. For an overview of the health effects of lead exposure, consult the Occupational Safety and Health Administration (OSHA) Appendix A of Occupational Exposure to Lead, 29 CFR 1910.1025.

EFFECTS OF OVEREXPOSURE *

ACUTE OVEREXPOSURE: Adverse health effects are not likely to occur

CHRONIC OVEREXPOSURE: Adverse health effects are not likely to occur

SECTION 4. FIRST AID MEASURES

EYES: If chemicals are gotten in the eyes, flush with copious quantities of water for at least 15 minutes. Get medical attention.

SKIN: Wash thoroughly with soap and water. If physical injury has occurred because of powerloads, get immediate medical attention.

INHALATION: Remove from exposure. Get medical attention if experiencing effects of overexposure. *



SECTION 5. EMERGENCY RESPONSE INFORMATION

IF PRODUCT IS INVOLVED IN FIRE: Use water. Fog type application to surrounding areas and other combustibles will reduce the potential for fire spread and will lower temperatures of the product.

FIREFIGHTERS: Must be protected from explosion of material. Normal fire fighting attire will provide limited protection at certain distances if product is packaged. Product may explode if heated above 200 degrees C.

TRANSPORTATION EMERGENCIES: Contact CHEMTREC at 1-800-424-9300. Consult the DOT Emergency Response Guidebook for instructions for handling emergencies involving this product.

SECTION 6. ACCIDENTAL SPILL/RELEASE MEASURES

Dry sweeping can contain spilled product. The recommended means for disposing of scrap is by incineration. Incineration must be at a fully permitted facility specifically designed and permitted in accordance with all applicable local, state, and federal regulations.

After scrapped by proper incineration, the remaining scrap materials should be disposed of or recycled in accordance with local, state, and federal regulations.

SECTION 7. HANDLING AND STORAGE PRECAUTIONS

Store in a cool dry place. Do not crush or drop packages. Avoid heat, electrical current, and acids. CCI-SPEER products are packaged and shipped in accordance with applicable Department of Transportation (DOT) rules. To ensure the highest level of safety while storing these products, keep product in the original packaging until ready to use. **Keep away from fire.**

SECTION 8. EXPOSURE CONTROL MEASURES

VENTILATION: Mechanical ventilation must be provided if necessary to keep the exposure levels below the exposure limits.

RESPIRATORS: If airborne concentrations exceed the Permissible Exposure Limit (PEL), wear respiratory protection in accordance with the OSHA Standard for Respiratory Protection, 29 CFR 1910.134.

HEARING PROTECTION: If noise levels exceed OSHA limits, while firing this product, use hearing protection in accordance with OSHA's Hearing Conservation Standard, 29 CFR 1910.95.

EYE PROTECTION: Wear ANSI-approved goggles or safety glasses.

HAND PROTECTION: NA

SKIN PROTECTION: If good personal hygiene practices are observed after firing this product, skin exposure problems are not anticipated.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Not Applicable	DECOMPOSITION TEMPERATURE	Not Applicable
FREEZING POINT:	Not Applicable	SOLUBILITY IN WATER	Not Applicable
BOILING POINT:	Not Applicable	EVAPORATION RATE	Not Applicable
SPECIFIC GRAVITY:	Not Applicable	MOLECULAR WEIGHT	Not Applicable
BULK DENSITY:	Not Applicable	VOLATILES, PERCENT BY VOLUME	Not Applicable
VAPOR PRESSURE:	Not Applicable	ODOR	Not Applicable
VAPOR DENSITY:	Not Applicable		

**SECTION 10. STABILITY AND REACTIVITY**

This product is normally stable. However, because of the design of ammunition and its components, partial detonation upon impact or intense heat may occur. Mass detonation will not occur. Keep away from fire.

SECTION 11. HANDLING AND DISPOSAL OF SCRAP

The recommended means for disposing of scrap is by incineration at a fully permitted facility specifically designed and permitted in accordance with all applicable local, state, and federal regulations.

After scrapped by proper incineration, the remaining scrap materials should be disposed of or recycled in accordance with local, state, and federal regulations.

SECTION 12. OTHER INFORMATION

The information in this MSDS was obtained from sources, which we believe are reliable. However, the information is provided without any representation or warranty, expressed or implied, regarding the accuracy or correctness.

The conditions or methods of handling, storage, use and disposal of this product are beyond our control and may be beyond our knowledge. For these and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use, or disposal of this product.